


JKM270M-60






MONO CRYSTALLINE MODULE

250-270 Watt

Jinko Solar introduces a brand-new line of high performance modules in wide application.




KEY FEATURES

-  Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)
-  Perfect module self-cleaning capability, reduce power loss caused by dust (soiling effect)
-  More elegant cell and module appearance
-  Excellent performance in low-light irradiance environment
-  High salt mist and ammonia resistance

QUALITY & SAFETY

- Positive power tolerance of -0/+3% *
- 10 year warranty on material & workmanship *
- Industry leading power output warranty (12 years/90%, 25 years/80%)
- Premium linear performance warranty *

Premium Performance Warranty



* Based on customer requirements and contract terms

ISO9001:2008、ISO14001:2004、OHSAS18001 certified factory
IEC61215、IEC61730、IEC61701、IEC62716 certified products

APPLICATIONS



On-grid residential roof-tops



On-grid commercial/industrial roof-tops




Solar power plants



Off-grid systems

Engineering Drawings




Packaging Configuration

(Two boxes = One pallet)

25pcs/ box , 50pcs/pallet, 700 pcs/40'HQ Container

Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	Mono-crystalline 156×156mm (6 inch)
No. of cells	60 (6×10)
Dimensions	1650×992×40mm (65.00×39.05×1.57 inch)
Weight	18.3 kg (40.4 lbs.)
Front Glass	3.2mm, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	TÜV 1×4.0mm, ² Length:900mm

SPECIFICATIONS

Module Type	JKM250M		JKM255M		JKM260M		JKM265M		JKM270M	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	250Wp	184Wp	255Wp	188Wp	260Wp	192Wp	265Wp	196Wp	270Wp	200Wp
Maximum Power Voltage (Vmp)	30.6V	28.3V	30.8V	28.5V	30.9V	28.6V	31.2V	28.9V	31.4V	29.2V
Maximum Power Current (Imp)	8.17A	6.51A	8.28A	6.60A	8.42A	6.71A	8.50A	6.78A	8.60A	6.85A
Open-circuit Voltage (Voc)	37.6V	34.7V	37.8V	34.9V	37.9V	35.0V	38.2V	35.3V	38.4V	35.5V
Short-circuit Current (Isc)	8.70A	7.02A	8.96A	7.21A	9.10A	7.32A	9.19A	7.39A	9.28A	7.45A
Module Efficiency STC (%)	15.27%		15.58%		15.89%		16.19%		16.50%	
Operating Temperature(°C)	-40°C~+85°C									
Maximum system voltage	1000VDC (IEC)									
Maximum series fuse rating	15A									
Power tolerance	0~+3%									
Temperature coefficients of Pmax	-0.41%/°C									
Temperature coefficients of Voc	-0.30%/°C									
Temperature coefficients of Isc	0.05%/°C									
Nominal operating cell temperature (NOCT)	45±2°C									

STC: Irradiance 1000W/m²

Cell Temperature 25°C

AM=1.5

NOCT: Irradiance 800W/m²

Ambient Temperature 20°C

AM=1.5

Wind Speed 1m/s

* Power measurement tolerance: ± 3%